



| Bearing Number | A | B | C | D | E | Bore | Load Rating |
|----------------|-------|-------|------|------|-------|-----------------|-------------|
| F-1272-4 | 1.272 | 11/32 | 7/32 | 9/16 | 1-3/8 | 0.255/0.252 | 47# |
| F-1272-4H | 1.272 | 11/32 | 7/32 | 9/16 | 1-3/8 | 0.257/0.253 Hex | 47# |
| F-1272-4HL | 1.272 | 13/32 | 9/32 | 5/8 | 1-3/8 | 0.257/0.253 Hex | 47# |
| F-1272-5 | 1.272 | 11/32 | 7/32 | 9/16 | 1-3/8 | 0.319/0.315 | 47# |
| F-1272-5H | 1.272 | 11/32 | 7/32 | 9/16 | 1-3/8 | 0.322/0.317 Hex | 47# |
| F-1272-5HL | 1.272 | 13/32 | 9/32 | 5/8 | 1-3/8 | 0.322/0.317 Hex | 47# |

A: Dimension Tolerance = +0.010/-0.000

| Bearing Number | A | B | C | D | E | Bore | Load Rating |
|----------------|-------|-------|------|------|-------|-----------------|-------------|
| F-1281-4 | 1.281 | 11/32 | 7/32 | 9/16 | 1-3/8 | 0.255/0.252 | 47# |
| F-1281-4H | 1.281 | 11/32 | 7/32 | 9/16 | 1-3/8 | 0.257/0.253 Hex | 47# |
| F-1281-4HL | 1.281 | 13/32 | 9/32 | 5/8 | 1-3/8 | 0.257/0.253 Hex | 47# |
| F-1281-5 | 1.281 | 11/32 | 7/32 | 9/16 | 1-3/8 | 0.319/0.315 | 47# |
| F-1281-5H | 1.281 | 11/32 | 7/32 | 9/16 | 1-3/8 | 0.322/0.317 Hex | 47# |
| F-1281-5HL | 1.281 | 13/32 | 9/32 | 5/8 | 1-3/8 | 0.322/0.317 Hex | 47# |

A: Dimension Tolerance = +0.010/-0.000

FEATURES

The bearings above have 11- 5/32" Diameter balls.

These bearings may be ordered with light oil or grease packed lubricant.

S added to the end of the part number designates an external rubber seal added to the front of the bearing.