



Bearing Number	A	B	C	D	E	Bore	Load Rating
F-1625-7H	1.625	23/64	11/64	17/32	1-3/4	0.451/0.450 Hex	135#
F-1665-7H	1.665	23/64	11/64	17/32	1-25/32	0.451/0.450 Hex	135#
F-1701-4	1.701	23/64	11/64	17/32	1-27/32	0.258/0.253	135#
F-1701-5	1.701	23/64	11/64	17/32	1-27/32	0.319/0.315	135#
F-1701-5H	1.701	23/64	11/64	17/32	1-27/32	0.322/0.317 Hex	135#
F-1701-6	1.701	23/64	11/64	17/32	1-27/32	0.382/0.377	135#
F-1701-6H	1.701	23/64	11/64	17/32	1-27/32	0.384/0382 Hex	135#
F-1701-7H	1.701	23/64	11/64	17/32	1-27/32	0.451/0.450 Hex	135#
F-1701-7HL	1.701	23/64	1/4	39/64	1-27/32	0.460/0.455 Hex	135#
F-1701-8	1.701	23/64	11/64	17/32	1-27/32	0.505/0.501	135#
F-1722-4	1.722	23/64	11/64	17/32	1-53/64	0.258/0.253	135#
F-1722-5	1.722	23/64	11/64	17/32	1-53/64	0.319/0.315	135#
F-1722-5H	1.722	23/64	11/64	17/32	1-53/64	0.322/0.317 Hex	135#
F-1722-7H	1.722	23/64	11/64	17/32	1-53/64	0.451/0.450 Hex	135#
F-1722-7H-1	1.722	23/64	9/32	43/64	1-53/64	0.451/0.450 Hex	135#
F-1775-4	1.775	23/64	11/64	17/32	1.900	0.258/0.253	135#
F-1775-5	1.775	23/64	11/64	17/32	1.900	0.319/0.315	135#
F-1775-5H	1.775	23/64	11/64	17/32	1.900	0.322/0.317 Hex	135#
F-1775-6	1.775	23/64	11/64	17/32	1.900	0.382/0.377	135#
F-1775-6H	1.775	23/64	11/64	17/32	1.900	0.384/0.382 Hex	135#
F-1775-7H	1.775	23/64	11/64	17/32	1.900	0.451/0.450 Hex	135#
F-1775-8	1.775	23/64	11/64	17/32	1.900	0.505/0.501	135#

A: Dimension Tolerance = +0.010/-0.000

FEATURES

The bearings above have 11- 1/4" Diameter balls.

These bearings may be ordered with light oil or grease packed lubricant.

T added to the end of the part number designates a nylatron seal added to the front of the bearing.

* Bore dimensions are interchangeable throughout the above bearings.