



Bearing Number	A	A1	B	C	D	E	Bore	Load Rating
<b>F-1710-7H</b>	1.715	1.670	33/64	1/4	47/64	1.800	0.460/0.455 Hex	180#
<b>FC-1710-7H</b>	1.715	1.670	33/64	1/4	47/64	1.800	0.460/0.455 Hex	252#
<b>FCR-1710-7H</b>	1.715	1.670	33/64	1/4	47/64	1.800	0.460/0.455 Hex	304#
<b>FH-1775-7H</b>	1.775	N/A	35/64	7/32	49/64	1.900	0.460/0.455 Hex	180#
<b>FC-1775-7H</b>	1.775	N/A	35/64	7/32	49/64	1.900	0.451/0.450 Hex	252#
<b>FCR-1775-7H</b>	1.775	N/A	35/64	7/32	49/64	1.900	0.451/0.450 Hex	304#

A and A1: Dimension Tolerance = +0.010/-0.000

## FEATURES

**F & FH** bearings have 12- 9/32” Diameter balls.

**FC** bearings have 13- 17/64” Diameter balls.

**FCR or MFCR** bearings have 8- 17/64” Diameter balls and a ball retainer for higher speed applications.

These bearings have a plastic insert which acts to quiet the bearing, also allowing it to be re-greased.

**M** at the beginning of the part number designates an all metal inner race.

The patented rib feature (**1710 Series only**) allows this bearing to be pressed into the roll without any secondary operation.

These bearings may be ordered with light oil or grease packed lubricant.

**S** added to the end of the part number designates a felt seal added to the front of the bearing.

**T** added to the end of the part number designates a Teflon<sup>1</sup> seal added to the front of the bearing.

<sup>1</sup> Teflon is a trademark of DuPont