



Bearing Number	A	B	C	D	E	Bore	Load Rating
FR-1498-7HDS	1.498	0.422	19/64	23/32	1.600	0.451/0.450 Hex	302#
FR-1498-7HIDS	1.498	0.422	7/32	41/64	1.600	0.451/0.450 Hex	302#
FR-1498-7H-1DS	1.498	0.422	17/32	63/64	1.600	0.451/0.450 Hex	302#
FR-1498-7H-2DS	1.498	0.422	9/32	25/32	1.600	0.451/0.450 Hex	302#
FR-1524-7HDS	1.524	0.422	19/64	23/32	1.625	0.451/0.450 Hex	302#
FR-1524-7HIDS	1.524	0.422	7/32	41/64	1.625	0.451/0.450 Hex	302#
FR-1524-7H-1DS	1.524	0.422	17/32	63/64	1.625	0.451/0.450 Hex	302#
FR-1524-7H-2DS	1.524	0.422	9/32	25/32	1.625	0.451/0.450 Hex	302#

A Dimension tolerance = +0.010/-0.000, B and E Dimension tolerance = +0.010/-0.010

FEATURES

The bearings above have 8- 7/32" Diameter balls and retainer.

These bearings are produced with a 16 teeth per inch knurl on the outside body of the bearing, (A Dimension), to assist in the assembly of the roll.

These bearings may be ordered with light oil or grease packed lubricant.

DS following the part number designates a front and a back seal. The **DS** is standard on the **FR** Series.

