



Bearing Number	A	B	C	D	E	Bore	Load Rating
FR-1775-7HRDS*	1.775	0.522	0.218	0.765	1.880	0.451/0.450 Hex	428#
FR-2265-10HRDS**	2.265	0.718	0.468	1.187	2.435	0.640/0.635 Hex	1050#
FR-2265-11HRDS**	2.265	0.718	0.468	1.187	2.435	0.703/0.698 Hex	1050#
FR-2265-11HVRDS**	2.265	0.718	0.218	0.937	2.435	0.703/0.698 Hex	1050#
FR-2280-10HRDS	2.280	0.718	0.468	1.187	2.435	0.640/0.635 Hex	1050#
FR-2280-11HRDS	2.280	0.718	0.468	1.187	2.435	0.703/0.698 Hex	1050#
FR-2280-11HVRDS	2.280	0.718	0.218	0.937	2.435	0.703/0.698 Hex	1050#

A Dimension tolerance = +0.010/-0.000. B, C, D and E Dimension tolerance = +0.010/-0.010

## FEATURES

The bearings above have 8- 17/64” Diameter balls and retainer.

These bearings are produced with a 16 teeth per inch knurl on the outside body of the bearing, (**A** Dimension), to assist in the assembly of the roll.

These bearings may be ordered with light oil or grease packed lubricant.

**DS** following the part number designates a front and a back seal. The **DS** is standard on the **FR** Series.

\* Not available in Carbon Steel

\*\* Stainless Steel is special order only—Call for quote