

Bearing Number	A	B	C	D	E	Bore	Load Rating
FR-1775-7HDS	1.775	0.422	7/32	43/64	1.880	0.451/0.450 Hex	428#
FR-1775-7H-1DS	1.775	0.422	11/32	15/16	1.880	0.451/0.450 Hex	428#
FR-1775-7HEDS	1.775	0.422	3/16	41/64	1.880	0.451/0.450 Hex	428#
FR-1775-7HFDS	1.775	0.422	19/64	23/32	1.880	0.451/0.450 Hex	428#
FR-1875-7HDS	1.875	0.422	7/32	43/64	1.980	0.451/0.450 Hex	428#
FR-1875-7H-1DS	1.875	0.422	11/32	15/16	1.980	0.451/0.450 Hex	428#
FR-1875-7HEDS	1.875	0.422	3/16	41/64	1.980	0.451/0.450 Hex	428#
FR-1875-7HFDS	1.875	0.422	19/64	23/32	1.980	0.451/0.450 Hex	428#
FR-2265-10HDS**	2.265	0.718	0.468	1.187	2.435	0.640/0.635 Hex	1050#
FR-2265-11HDS**	2.265	0.718	0.468	1.187	2.435	0.703/0.698 Hex	1050#
FR-2265-11HVDS**	2.265	0.718	0.218	0.937	2.435	0.703/0.698 Hex	1050#
FR-2280-10HDS	2.280	0.718	0.468	1.187	2.435	0.640/0.635 Hex	1050#
FR-2280-11HDS	2.280	0.718	0.468	1.187	2.435	0.703/0.698 Hex	1050#
FR-2280-11HVDS	2.280	0.718	0.218	0.937	2.435	0.703/0.698 Hex	1050#

A Dimension tolerance = +0.010/-0.000, B and E Dimension tolerance = +0.010/-0.010

FEATURES


The bearings above have 8- 17/64” Diameter balls and retainer.

These bearings are produced with a 16 teeth per inch knurl on the outside body of the bearing, (A Dimension), to assist in the assembly of the roll.

These bearings may be ordered with light oil or grease packed lubricant.

DS following the part number designates a front and a back seal. The **DS** is standard on the **FR** Series.

**** Stainless Steel is special order only – Call for quote**



NOTE: INNER RACE IS EXTENDED ON BOTH SIDES OF FR-XXXX-7H-1DS ONLY